

ROLLEX MEDICAL (AUST) PTY LTD

PO Box 170 | Mt Kuring-gai 2080 | Sydney, NSW | Australia

Phone: 1300 880 441 | Fax: 1330 880 451

Email: sales@rollexmedical.com | www.rollexmedical.com.au

The Matos[®] Plus Eco fridge series is a new range of purpose built Medical and Vaccination Refrigerators utilising patented technology. The cabinet and componentry have been specially designed for use in the Medical field.

Model Variations

Eco 200 R/DT – Solid Door, hot gas defrost Eco 200 R/GDT – Glass Door, hot gas defrost





Interior Finish

All Matos° Plus Eco fridges come with a high quality aluminium interior and use polyurethane foam thermal insulation. A stainless steel interior is also offered as an option.

Lock Fitted as Standard

Maintains security and ensures the unit can only be opened by authorised personnel.

Solid or Glass Door Options

Most models come with solid or glass door options enabling you to select the format which best suits your requirements.

Auto Defrost

The advanced controller initializes a regular defrost sequence to decrease the chance of ice build-up while maintaining the temperature below 8°C. Matos* Plus Eco fridges can also be ordered with a gas defrost capability.

Energy Efficient

Matos[®] Plus Eco fridges are more energy efficient and kinder to the environment, meaning the running costs of the refrigerator are kept as low as possible.

3 Year Extended Warranty

When serviced by an approved service technician, the warranty is extended to 3 years.

CCTC / QCPP Certified

CCTC and QCPP Approved Vaccine Pharmacy Graded Refrigerator.

Specifications

Capacity	200L	Power	170W
Dimensions External	620w x 1060h x 650d	Air convection	Forced Air
Dimensions Internal	520w x 860h x 420d	Temperature range	0°C – +10°C
Max shelf workload	10kg	Controller	Microprocessor with external LCD graphic display
Max unit workload	40kg	Interior	Aluminium (s/steel optional)
Door	Solid/Glass option	Housing	Powder coated sheet (s/steel optional)
Weight	52kg	Temperature resolution	0.1°C
Shelves fit/max	3/4	Temperature fluctuation at 4°C	+/- 0.5°C
Gas defrost	Optional	Voltage 50/60Hz	115/230V
Refrigerant	R134A	Internal light	Yes
Refrigerant amount	0.065kg	Door Open Alarm	Yes
Castors	Optional	Access Port	Yes