

ROLLEX MEDICAL (AUST) PTY LTD  
 PO Box 170 | Mt Kuring-gai 2080 | Sydney, NSW | Australia  
 Phone: +61 2 9457 6144 | Fax: +61 2 9457 6516  
 Email: sales@rollexmedical.com | www.rollexmedical.com.au

## Model Variations

- MATOS Aria Eco 300 R – Solid Door
- MATOS Aria Eco 300 R/G – Glass Door



MATOS Aria Eco 300 R

The MATOS® Aria Eco fridge series is a new range of cost-effective European-built Medical and Vaccination Refrigerators featuring the latest technology in controllers and compressors for accurate temperature stability.

### Advanced Controller

Featuring the Carel soft touch controller - accurate to 0.1°C with min/max readings at the touch of a button.

### Lock Fitted as Standard

Maintains security and ensures the unit can only be opened by authorised personnel.

### Cost-Effective

Built with a High Impact Polystyrene Interior to provide a robust and in-expensive range of refrigerators.

### Solid or Glass Door Options

Solid or glass door options enabling you to select the format which best suits your requirements. Glass doors are double glazed, toughened safety-glass with argon gas between panels for better insulation.

### Auto Defrost

The advanced controller initialises a regular defrost sequence to decrease the chance of ice build-up while maintaining the temperature below 8°C.

### Extended Warranty

Standard 12 month warranty however an extended warranty option is available subject to Terms and Conditions

### CCTC / QCPP Certified

CCTC and QCPP Approved Vaccine Pharmacy Graded Refrigerator.



## Specifications

Capacity	269L Net / 290L Gross	Power usage	Solid 2.9kW Glass 3.6 kW / 24 hours
Dimensions external	597w x 645d x 1785h	Air convection	Fan assisted
Dimensions internal	505w x 462d x 1355h	Operating range	1°C to +10°C
Door	Solid and Glass available Reversible	Controller	Microprocessor with external LCD graphic display
Weight	Solid 65kg / Glass 74kg	Interior/Exterior	(HIPS) High impact polystyrene
Shelves fitted	6	Temperature resolution	0.1°C
Castors	2 wheels rear, 2 adjustable feet front	Temperature fluctuation at 4°C	+/- 0.5°C
Internal light	Yes	Refrigerant	R134A
Door Open Alarm	Yes	Power	230V / 50Hz
Noise Level dB	46.8		